

# Lasair III®

Aerosol Particle Counter Models

AVAILABLE WITH  
**ISO 17025**  
CALIBRATION  
for select parameters



The Lasair III Particle Counter sets the standard for portable aerosol particle counters, and fully meets the requirements of ISO 14644-1 (including the new 2015 revision) and ISO 21501-4.

The Lasair III Particle Counter is available in three different flow rate configurations (1 CFM, 50 LPM and 100 LPM) to meet a variety of cleanroom applications. It can be used for routine remote and mobile cleanroom monitoring. Interactive software steps the user through the ISO 14644-1 (including the latest 2015 revision), EC GMP Annex 1, China GMP, and FS 209E room certification process.

Cleanroom certification results are available through a local printout, downloadable via USB in a secure format, or through the use of external software packages such as DataAnalyst, Facility Net or Pharmaceutical Net software.

The user interface is facilitated by the use of a large, easy-to-read IR touchscreen that works with gloves—no stylus required. Interaction problems commonly associated with resistive or capacitive touchscreens are eliminated.

The rugged chemical-resistant enclosure is lightweight for portability. The instrument's streamlined design minimizes particle traps, making the unit easy to clean. Power is provided to the unit through the use of the on-board hot-swappable batteries. Power can also be provided through the use of an external AC power source, which can simultaneously power the unit and charge the on-board batteries.

The Lasair III Particle Counter accepts inputs from a wide range of environmental sensors through the four built-in 4-20 mA inputs. Wireless network communications are made easy with an externally-mounted wireless adapter, simplifying communications with network systems. The unit can be remotely managed via the built-in Web browser function, through Ethernet or with the integrated Modbus TCP/IP communication protocol, and can connect with Pharmaceutical Net, Facility Net, FacilityPro®, or any other third party monitoring software.

## BENEFITS

- Comprehensive validation manual makes it easy to meet pharmaceutical regulatory requirements
- Operates in cleanrooms via a Web browser: Set up, sample, display, print, download data
- Removable batteries with optional external charger for continuous mobile use
- Stores sampling recipes to reduce operator errors
- Long-term data archiving with DataAnalyst software
- Local printout for immediate hardcopy results
- USB electronic printouts for long term storage
- CSV file download for easy data integration
- Interactive software steps the user through the ISO 14644-1, EC GMP Annex 1, China GMP and FS 209E room certification process
- Up to 32 customizable alarm comments for easier cleanroom problem identification
- Modbus TCP/IP communication protocol for a wider integration with third party monitoring systems
- Quiet pump improves work environment
- 21 CFR Part 11 compliant download

## FEATURES

- 100 LPM, 50 LPM, or 1 CFM flow rates available
  - 100 LPM flow samples 1 m<sup>3</sup> in 10 minutes
- ISO 21501-4 compliant with a built-in Pulse Height Analyzer (PHA). Available with ISO 17025 calibration certificate. (Optional)
- Large, 8.4 inch IR touchscreen can be used when wearing gloves for simplified use
- Calculates and creates reports for ISO 14644-1:1999, ISO 14644-1:2015, EC GMP Annex 1, China GMP, and FS 209E
- Access via a Web browser
- Compatible with common cleanroom cleaning chemicals
- Choose from 12 languages for display and printout
- ISO14644-1:2015 Compliant

## APPLICATIONS

- Cleanroom monitoring
- Facility certification for ISO 14644-1:1999 & 2015, EC GMP, China GMP, FS 209E
- Trend analysis
- Statistical process control
- Troubleshooting particle excursions
- Manifold compatible
- Portable or dedicated use



**PARTICLE  
MEASURING  
SYSTEMS®**  
pmeasuring.com

*Without measurement there is no control*

# Lasair III<sup>®</sup>

## Aerosol Particle Counter Models

## Specifications

	<b>310B, 310C</b>	<b>350L</b>	<b>5100</b>
<b>Channels</b>	310B: 0.3, 0.5, 1.0, 3.0, 5.0, 10.0 µm 310C: 0.3, 0.5, 1.0, 5.0, 10.0, 25.0 µm	0.3, 0.5, 1.0, 5.0, 10.0, 25.0 µm	0.5, 1.0, 2.0, 5.0, 10.0, 25.0 µm
<b>Flow Rate</b>	1.0 CFM (28.3 LPM) ± 5%	50 LPM ± 5%	100 LPM ± 5%
<b>Calibration</b>	Meets ISO 21501-4 requirements - ISO 17025 Compliant Certification available (Optional)		
<b>Maximum Concentration<sup>a</sup></b>	> 1,380,270/ft <sup>3</sup>	> 832,599/ft <sup>3</sup>	> 688, 495/ft <sup>3</sup>
<b>Counting Efficiency</b>	50% ± 20% for most sensitive threshold. Meets ISO 21501-4 requirements.		
<b>Zero Count</b>	7.07 counts/m <sup>3</sup> (1CFM); 4.00 counts/m <sup>3</sup> (50 LPM); 2.00 counts/m <sup>3</sup> (100 LPM)		
<b>Data Storage</b>	3,000 complete data sets. 21 CFR 11 compliance. Long-term data storage/analysis with DataAnalyst.		
<b>Communication Modes</b>	Ethernet, Modbus TCP/IP, or RS-232; USB data downloading; optional wireless Ethernet		
<b>Controlling Software</b>	Facility Net, Pharmaceutical Net, FacilityPro, Microsoft <sup>®</sup> Internet Explorer <sup>®</sup> 5.0+, Firefox <sup>®</sup>		
<b>Remote Operation</b>	Remote web browser operation; real-time download to Facility Net or Pharmaceutical Net, or Modbus TCP/IP based monitoring systems		
<b>Reports</b>	USB reports; sample printouts; cleanroom certification reports for ISO 14644-1:1999 & 2015, EC GMP, and FS 209E; averaging		
<b>Environmental Sensors</b>	Four 4-20 mA inputs		
<b>Languages</b>	English, French, German, Italian, Japanese (Kanji), Korean, Spanish, Chinese (traditional or simplified), Russian, Portuguese, Polish		
<b>Display and Printer</b>	8.4" color VGA display (640 x 480); IR touch screen (IP65 rated); built-in thermal printer		
<b>External Surface</b>	Polycarbonate (PC)		
<b>Enclosing Cleaning Materials</b>	Bleach, ethyl/isopropyl alcohol, peroxide/quaternary ammonium solutions		
<b>Sample Tubing ID<sup>b</sup></b>	3/8", 8 m max. length	1/2", 8 m max. length	3/4", 8 m max. length
<b>Sample Output Filtering</b>	Internally filtered to > 99.97% at 0.3 µm		
<b>Power and Battery<sup>c</sup></b>	100 – 264 V, 50 – 60 Hz, 150 W Lithium battery: estimated operation 3 hr (single) 6 hr (dual) for 1 CFM unit		
<b>Dimensions (H x W x L)</b>	11.9 x 12.9 x 10.2 in (30.1 x 32.7 x 25.9 cm)		
<b>Weight</b>	13.2 lb (6 kg) without battery, 16.5 lb (7.5 kg) with two optional batteries		
<b>Operating Environment</b>	Temperature: 32 – 86 °F (0 – 30 °C); Humidity: 5 – 95% RH non-condensing		

All dimensions, weights and values not provided with a tolerance are +/-10% values.

a. Less than 10.0% coincidence loss at maximum recommended concentration.

b. For pharmaceutical applications, tubing length should equal 2m maximum.

c. Battery life is based on continuous operation running one (1) minute samples and printing every minute.

FacilityPro<sup>®</sup> and Lasair<sup>®</sup> are registered trademarks of Particle Measuring Systems, Inc.

Internet Explorer<sup>®</sup> and Microsoft<sup>®</sup> are registered trademarks of Microsoft Corporation.

Firefox<sup>®</sup> is a registered trademark of Mozilla.

All other trademarks are the property of their respective owners.

Patent details available at: [pmeasuring.com/trademarks-patents](http://pmeasuring.com/trademarks-patents).

Particle Measuring Systems, Inc. reserves the right to change specifications without notice.

### HEADQUARTERS

5475 Airport Blvd  
Boulder, Colorado 80301 USA  
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support  
E: +1 800 557 6363  
Customer Response Center  
T: +1 877 475 3317  
E: [info@pmeasuring.com](mailto:info@pmeasuring.com)

### GLOBAL OFFICES

BRAZIL  
T: +55 11 5188 8227  
E: [pmsbrazil@pmeasuring.com](mailto:pmsbrazil@pmeasuring.com)

CHINA  
T: +86 21 6113 3600  
E: [pmschina@pmeasuring.com](mailto:pmschina@pmeasuring.com)

FRANCE  
T: +33 (0)6 82 99 17 98  
E: [pmsfrance@pmeasuring.com](mailto:pmsfrance@pmeasuring.com)

GERMANY  
T: +49 6151 6671 632  
E: [pmsgermany@pmeasuring.com](mailto:pmsgermany@pmeasuring.com)

ITALY  
T: +39 06 9053 0130  
E: [pmsssl@pmeasuring.com](mailto:pmsssl@pmeasuring.com)

JAPAN  
T: +81 3 5298 8175  
E: [pmsjapan@pmeasuring.com](mailto:pmsjapan@pmeasuring.com)

KOREA  
T: +82 31 286 5790  
E: [pmskorea@pmeasuring.com](mailto:pmskorea@pmeasuring.com)

MEXICO  
T: +52 55 2271 5106  
E: [pmsmexico@pmeasuring.com](mailto:pmsmexico@pmeasuring.com)

NORDIC  
T: +45 707 028 55  
E: [pmsnordic@pmeasuring.com](mailto:pmsnordic@pmeasuring.com)

PUERTO RICO  
T: +1 787 718 9096  
E: [pmspuertorico@pmeasuring.com](mailto:pmspuertorico@pmeasuring.com)

SINGAPORE  
T: +65 6496 0330  
E: [pmsingapore@pmeasuring.com](mailto:pmsingapore@pmeasuring.com)

TAIWAN  
T: 886-3-5525300 Ext: 301  
E: [pmstaiwan@pmeasuring.com](mailto:pmstaiwan@pmeasuring.com)

UNITED KINGDOM  
T: +44 1684 581 000  
E: [pmsemea@pmeasuring.com](mailto:pmsemea@pmeasuring.com)

