

# Validator® 2000

## PRODUCT ADVISORY NOTICE

WITH THE INTRODUCTION OF VALPROBE RT WIRELESS SYSTEM, KAYE GIVES YOU MORE REASONS THAN EVER TO UPGRADE YOUR VALIDATOR 2000.



Validator® 2000

Validator® AVS



ValProbe® RT

### VALIDATOR 2000 CHALLENGES

The Validator 2000 served the market well for 20+ years, but has been phased out due to new challenges:

- Discontinued in 2016 and spare parts cannot be guaranteed after December 2021
- Data integrity challenges with new and updated

data requirements

- Windows no longer supports the operating system on Validator 2000s

Note that Kaye will continue, as we've always done, to service your Validator 2000 as long as parts are available, and that we will continue to calibrate them.

## VALIDATOR® AVS – REVOLUTIONARY WIRED SOLUTION

Upgrading your Validator 2000 to the Validator AVS will speed up all of your qualifications, calibrations, and validations. Unlike the Validator 2000, the AVS come equipped with:

- Dedicated portable tablet for reviewing all validation tasks
- New wiring layout and pass / fail report
- Unprecedented accuracy in sensor measurements with all GMP requirements for calibration and traceability
- Performs multi-point verification set points to qualify multiple chambers at different temperatures at the same time



## VALPROBE® RT – REAL-TIME WIRELESS SOLUTION

Kaye ValProbe RT wireless data loggers allow you to perform thermal validations without the need of any thermocouples, or even being connected to your asset.

- Wide range of bendable, rigid, flexible, surface, pressure, and humidity loggers and sensors
- Analyze validation data in real time from up to 150 meters away
- Wide temperature range from -85°C to 400°C
- Handle up to 100,000 samples per sensor
- Has a scan rate down to 1 second and a data transmission rate of 3 seconds to 30 seconds

### Kaye Representative contact:

### Request a demo:

**EUROPE, MIDDLE EAST, AFRICA AND ASIA**  
Amphenol Advanced Sensors Germany GmbH  
Sinsheimer Strasse 6  
D-75179 Pforzheim  
T: +49 (0) 7231-14 335 0  
F: +49 (0) 7231-14335 29  
Email: [kaye@amphenol-sensors.com](mailto:kaye@amphenol-sensors.com)

**USA / AMERICAS**  
Amphenol Thermometrics, Inc.  
967 Windfall Road  
St. Marys, PA 15857  
T: +1(814) 834-9140  
F: +1(814) 781-7969  
Email: [kaye-us@amphenol-sensors.com](mailto:kaye-us@amphenol-sensors.com)

#### ENVIROTERM SDN. BHD.

**HEAD OFFICE**  
Lot 5035, Jalan 18/62,  
Taman Perindustrian Sri  
Serdang, 43300 Seri  
Kembangan,  
Selangor D.E., Malaysia.  
T: +603 8210 8338  
E: [sales@envirotech.com](mailto:sales@envirotech.com)



**NORTHERN OFFICE**  
5112, Jalan Capri,  
Taman Capri,  
12100 Butterworth,  
Pulau Pinang,  
Malaysia.  
T: +604 331 1371  
F: +604 331 1373

**SOUTHERN OFFICE**  
37-1 Jalan Setia Tropika,  
Taman Setia Tropika 1/25,  
81200 Johor Bahru,  
Johor D.T., Malaysia.  
T: +607 236 2768  
F: +607 236 2769



**Warranty and disclaimer:** The information mentioned on documents are based on our current tests, knowledge and experience. Because of the effect of possible influences in an application of the product, they do not exempt the user from their own tests, checks and trials. A guarantee of certain properties or a guarantee for the proper suitability of the product for a specific, especially permanent application can not be derived from our data. Liability is therefore excluded to that extent permitted by law. Any proprietary rights of third parties as well as existing laws and regulations must be observed by the recipient of the product on his own responsibility.

© 2023 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.