

HPGP™ 101-C

Ultra High Purity Gas Particle Counter and PDS-E

Provides reliable in-line contamination monitoring for process gases at line pressure

Without measurement there is no control



High-technology manufacturing processes often require high-purity gases. The HP GP 101-C provides reliable in-line contamination monitoring for process gases at line pressure.

The HP GP is compatible with most non-toxic gases and can be used in many reactive gas monitoring applications.

The PDS-E (Particle Data System - Ethernet) instrument collects and reports data captured by the HP GP 101-C probe.

Particle Counter	CDA	N ₂	Ar	CO ₂	O ₂ /He/ Ne/ H ₂
Airnet	Y	Y	N	N	N
Lasair III 110	Y	Y	N	N	N
Lasair III 310	Y	Y	Y	N	N
IsoAir 310P	Y	Y	Y	N	N
IsoAir Pro-E/Plus	Y	Y	Y	Y	N
Lasair Pro	Y	Y	Y	Y	N
HP GP 101-C	Y	Y	Y	Y	Y

BENEFITS

Reduced Cost

- Speed qualification of process gas distribution systems
- Detect particles in gases before they impact yield
- Compatible with oxygen, hydrogen, and most non-toxic gases

Improved Process Control

- Verify gas quality
- Detect process upsets
- Quantify impact of system changes
- Accurate particle sizing
- Facility Net data management software for comprehensive data storage, management, reports, and alarms

Reliable

- Passive cavity design requires infrequent maintenance
- Inert gas purge ensures safety
- Leakage of sample gas to vessel discontinues power to electronics

FEATURES

- 0.1 µm sensitivity at 0.1 SCFM
- 8 particle channels
- Line pressures from 40 to 150 psig
- Passive laser cavity
- Parallel processing array detector system
- Safety containment vessel
- Oxygen and hydrogen compatibility
- CE and RoHS 2 compliant

APPLICATIONS

- Qualification of gas distribution systems
- Process gas monitoring
- Reactive gas monitoring



HPGP™ 101-C

Ultra High Purity Gas Particle Counter and PDS-E

Specifications

HPGP 101-C

Size channels	8 channels with thresholds at: 0.1, 0.2, 0.3, 0.5, 1.0, 2.0, 3.0, 5.0 µm
Sample rate	0.1 SCFM (2.8 LPM) (=total volumetric flow rate)
Counting efficiency*	> 50% at 0.14 µm
Zero count level	< 2/ft³ or < 0.2/min
Maximum concentration**	3,000/ft³
Laser type	HeNe
Calibration	Traceable to the US National Institute of Standards and Technology (NIST).
Power	100, 115, 220 – 230, or 230 – 240 V, 50 – 60 Hz, 0.5 A
Environment	Temperature: 32 – 113 °F (0 – 45 °C). Humidity: non-condensing. Maximum altitude: 9,842 ft (3,000 m).
Dimensions (l, w, h)	26 x 8 x 9 in (66 x 20 x 22 cm)
Weight	45 lb (20.4 kg)
Compliance	CE, RoHS 2

PDS-E (Data Interface)

Number of sensors	Supports 1 HPGP unit per PDS-E
Sampling interval	1 sec to 8 hr
Computer interface	RS-232, bi-directional; Ethernet (via PMS protocol, Modbus, or OPC)
Power	100 – 240 VAC, 50 – 60 Hz, 0.63 A
Environment	Temperature: 32 – 113 °F (0 – 45 °C), Humidity: non-condensing, Maximum altitude: 9,842 ft (3,000 m)
Dimensions (l, w, h)	7 x 8.5 x 12.5 in (18 x 22 x 32 cm)
Weight	11.5 lb (5.2 kg)

* Allow ± 5% for variations in sample flow.

** Greater than 90% accuracy (less than 10% coincidence loss) at maximum recommendation ambient concentration.

Patents apply: United States – 4,798,465, 4,893,928, and 4,594,715. Japan – 2,786,187, and 2,554,614.
Germany – 3,712,665C2, 3,930,642, and 3,485,749.4. Canada – 1,228,148. UK – EP142815.

HEADQUARTERS

5475 Airport Blvd
Boulder, Colorado 80301 USA
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support
T: +1 800 557 6363

Customer Response Center
T: +1 877 475 3317
E: info@pmeasuring.com

www.pmeasuring.com
info@pmeasuring.com



MALAYSIA DISTRIBUTOR

ENVIROTERM SDN. BHD.
HEAD OFFICE
Lot 5035, Jalan 18/62,
Taman Perindustrian Sri Serdang,
43300 Seri Kembangan,
Selangor D.E., Malaysia.

T: +603 8210 8338
F: +603 8943 6012
E: sales@enviroterm.com
W: www.enviroterm.com

NORTHERN OFFICE

5112, Jalan Capri,
Taman Capri,
12100 Butterworth,
Pulau Pinang, Malaysia.

T: +604 331 1371
F: +604 331 1373
E: sales@enviroterm.com
W: www.enviroterm.com

SOUTHERN OFFICE

37-1, Jalan Setia Tropika,
Taman Setia Tropika 1/25,
81200 Johor Bahru,
Johor D.T., Malaysia.

T: +607 236 2768
F: +607 236 2769
E: sales@enviroterm.com
W: www.enviroterm.com

© 2018 Particle Measuring Systems, Inc. All rights reserved.
2018.10



All trademarks are the property of their respective owners. Particle Measuring Systems, Inc. reserves the right to change specifications without notice. © 2022 Particle Measuring Systems, Inc. All rights reserved. 09212022