

MiniCapt® Mobile

Mobile Microbial Air Sampler

Innovative, light mobile air sampler applying modern data management capabilities

Without measurement there is no control



The MiniCapt® Mobile Microbial Air Sampler allows the user to perform viable air sampling in cleanroom environments for classification and monitoring purposes.

The sampler's housing and touchscreen have antibacterial properties limiting introduction of contamination from the device in line with current regulatory standards. Microbial activity testing was performed with *S. aureus* and *E. coli*, and saw a reduction of greater than 95% compared to previous models.

Available in three flowrate models, the MiniCapt Mobile sampler is designed for any cleanroom, including critical environments such as ISO Class 5 and GMP Grade A.

This top tier instrument incorporates modern data management capabilities and an easy, interactive touchscreen interface. Connected with the latest DataAnalyst software, users can manage sampling data and microbial counts in a complete paperless solution. Data is secure with uneditable file exports. Connecting to several accessories is easy, and cleanroom contamination is avoided with built-in HEPA filtration.

The impactor head design has 20 precision-cut radial slits and an adjustable height and plate diameter mechanism that allow the MiniCapt Mobile sampler to be used with almost all manufactured agar plates, including glass Petri plates. The radial slits also ensure laminar flow, making false positive identification easier.



**PARTICLE
MEASURING
SYSTEMS®**
a spectris company

envirotecm

BENEFITS

Flexibility

- Multiple applications (isolator sampling, compressed gases, remote and handheld usages)
- Operates with BioCapt® Single-Use units
- Adjustable height and diameter mechanism for versatile Petri dish compatibility (86 - 92 mm)

Precision

- Meets ISO 14698-1
- Radial slit design for optimal microorganism recovery during sampling
- Immediate and easy detection of false-positive results
- Feller correction only above 57 CFU, max 3% overlap deviations at 200 CFU

Security

- Antibacterial housing and touchscreen
- HEPA-filtered exhaust ensures no environmental contamination of critical control points
- Autoclavable 316L stainless steel impactor head

FEATURES

- Modern data and sample configuration management
- Multiple levels of security
- Management of microbial counts and data analysis with DataAnalyst software (Version 3.0+)
- Uneditable data records, reports and file exports
- Error reduction with intuitive user interface and pre-configured sampling recipes

APPLICATIONS

- Microbial air sampling in cleanrooms and associated controlled environments
- USP 797 environmental viable-airborne particle testing
- Microbial monitoring of medical device manufacturing environments

MiniCapt® Mobile

Mobile Microbial Air Sampler

Specifications

MiniCapt	25M	50M	100M
Sampling flow rate	25 Liters/minute	50 Liters/minute	100 Liters/minute
Battery (Lithium ion) ¹	12 hours	7 hours	6 hours
Power supply	Input: 100 – 240 VAC, 50/60 Hz, 1.5 A		
Memory	3,000 Samples; 400 Areas/Locations; 50 Recipes		
Sampling modes	Volume or Time; Interval sampling		
Sampling interval			
Time:	1 – 400 min	1 – 200 min	1 – 100 min
Volume:	1 – 9999 L	1 – 9999 L	1 – 9999 L
Communication	Modbus TCP; USB for data download; USB for printer connection		
Display	4.3" VGA (480 x 272) LCD with touchscreen		
Display Languages	English, French, German, Italian, Japanese, Korean, Spanish, Chinese (traditional or simplified), Russian, Portuguese		
Dimensions (h, w, d)	10.2 x 5.7 x 5.9 in (26.0 x 14.5 x 15.0 cm)		
Weight	4.6 lb (2.1 kg)		
Operating environment	Temperature: 32 – 104 °F (0 – 40 °C); Humidity: 10 – 90% RH		
Calibration interval	Recommended every 12 months		

¹Battery life based on sampling 10 minutes, pausing 5 minutes, and repeating.

BioCapt Impactor Head

Materials	AISI 316L Stainless Steel
Number of Inlets	20 (Precision-cut slits)

Accessories

Compressed Gas Sampling Kit
Isolator Monitoring Kit
Base Mounting Kit
Remote Sampling Kit for BioCapt Adjustable Height
Remote Sampling kit for BioCapt Single-Use
Remote ISP Sampling Kit
Petri Dish Barcode Reader
External Printer Kit

Accessories

Compressed Gas Sampling Kit



Isolator Monitoring Kit



Remote ISP Sampling Kit



Base-mounted MiniCapt Mobile



Remote connection to BioCapt® Single-Use



HEADQUARTERS

5475 Airport Blvd
Boulder, Colorado 80301 USA
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support
T: +1 800 557 6363

Customer Response Center
T: +1 877 475 3317
E: info@pmeasuring.com

www.pmeasuring.com
info@pmeasuring.com



MALAYSIA DISTRIBUTOR

ENVIROTERM SDN. BHD.
HEAD OFFICE
Lot 5035, Jalan 18/62,
Taman Perindustrian Sri Serdang,
43300 Seri Kembangan,
Selangor D.E., Malaysia.

T: +603 8210 8338
F: +603 8943 6012
E: sales@enviroterm.com
W: www.enviroterm.com

NORTHERN OFFICE

5112, Jalan Capri,
Taman Capri,
12100 Butterworth,
Pulau Pinang, Malaysia.

T: +604 331 1371
F: +604 331 1373
E: sales@enviroterm.com
W: www.enviroterm.com

SOUTHERN OFFICE

37-1, Jalan Setia Tropika,
Taman Setia Tropika 1/25,
81200 Johor Bahru,
Johor D.T., Malaysia.

T: +607 236 2768
F: +607 236 2769
E: sales@enviroterm.com
W: www.enviroterm.com

