UV-CHAMBER BER

• Light polymerization of plastics

UV purification

 Drying and hardening of glues, lacquering and polymerisation of synthetic materials

· Artificial ageing

• Ageing and erasing EPROMS

 Micro cleaning (with ozone radiation)



just clean - with UV

UV-CHAMBER



Use of the UV-chamber

Dinies UV chambers can be equipped with UV lamps of different wavelengths, whereby the equipment is very flexible and suitable for the most diverse applications.

On account of the low operating temperature of up to 40°C of the low-pressure lamps used, in contrast to medium or high-pressure lamps, in which temperatures can reach 800°C, temperature-sensitive materials can be brought very close to the radiation source.

This increases significantly the UV intensity on the surface of the parts and thus reduces production time.

The exposure time is adjusted by means of a mechanical (4hrs) or electronic (999hrs) timer.

Through use of a smooth-running drawer the materials are simply and safely transferred under the UV lamp. For safety reasons, the lamps switch off but when opening the drawer they are reactivated.

Advantages

- Robust construction
- Ideal for laboratory and production
- Can be fitted with lamps of various wavelengths
- High radiation intensity with low heat production lamp
- Control of heat production
- Environmentally-friendly purification without chemicals









handed out by:

Technical Data

Model	ELG100S	M1	M2	M3
Rated Voltage	230V/50Hz	230V/50Hz	230V/50Hz	230V/50Hz
Rated power	40W	100W	200W	300W
Dimensions wxhxd [mm]	175x83x306	225x155x255	425x155x255	425x155x464
Weight [kg]	3,2	4,0	7,3	11,0
Admission [mm]	14	45	45	45
Radiation area [mm] LxB	225x150	220x195	220x395	429x395
Timer	Mechanical 0-4hrs	Electronic 0-999hrs	Electronic 0-999hrs	Electronic 0-999hrs
Operating hours counter	-	yes	yes	yes
UV-power UVA (365nm) mW/cm²	8	7	7	8
UV-power UVB (320nm) mW/cm²	-	-	-	6
UV-power UVC (254nm) mW/cm²	15	18	18	18
UV-power Ozon (185nm) mW/cm ²	√*1	√*1	√*1	√*1

(*1): UV power for ozone lamps is not relevant, the ozone production is strongly influenced by the degree fo absorption of the test object, etc.