

ValProbe® RT

NEWEST STATE-OF-THE-ART TECHNOLOGY WIRELESS
REAL-TIME TEMPERATURE, HUMIDITY AND PRESSURE
DATA COLLECTION



Enhance Your Process Visibility with Real-Time Insights

Kaye ValProbe® RT (Real-Time) is a wire-free real-time process validation and monitoring system designed around the measurement and reporting requirements of the most intensely regulated industries.

It is a state-of-the-art validation system design that meets industry and regulatory (FDA/GAMP) requirements for thermal validation. The ValProbe RT system combines high accuracy measurements, automated sensor calibration, an intuitive metro style user interface, and extensive reporting to simplify the complete validation process.

Kaye ValProbe RT is the successor of the widely recognized Kaye ValProbe, the accepted standard in wireless validations systems for over 15 years.

The ValProbe RT family of data loggers provide accurate, convenient, and reliable process measurement for a wide range of pharmaceutical and medical device applications. The wireless design greatly simplifies monitoring and validation of severe and hard-to-reach environments. See the table below for logger types and recommended applications.

	Temperature Rigid Logger	Temperature Flexible Logger	Temperature Bendable Logger	Temperature Freeze Dryer Logger	Pressure / Temperature Logger	Humidity / Temperature Logger	CO ₂ / Humidity / Temperature Logger
Steam Sterilizers	✓	✓	✓	✓	✓		
Dry Heat Sterilizers			✓				
Steam in Place (SIP)	✓	✓	✓		✓		
Water Cascade / Fall Sterilizer	✓	✓	✓	✓	✓		
Incubators / Bioreactors	✓	✓	✓			✓	✓
Stability Chambers	✓	✓	✓			✓	
Freezers	✓	✓	✓	✓			
Freeze Dryer / Lyophilization	✓	✓	✓	✓			
Vessels	✓	✓	✓		✓		

Lifting Real Time Validation to the Next Level

The Kaye ValProbe RT System is a unique design and concept combining a ValProbe RT system with a Validation Console. The console is a rugged, hardened tablet to interface with your Kaye ValProbe RT and legacy hardware. It is pre-loaded with Kaye software and specifically engineered for validation tasks only. This concept greatly simplifies software validation and dependency on continuously changing PCs, operating systems, and core loads. The Kaye ValProbe RT offers easy, dedicated and reliable validation. The Kaye ValProbe RT is intuitive, efficient, and easy to operate – allowing you to focus on the validation, not the technology.

Kaye ValProbe RT Logger simplifies access to hostile, remote, and hard-to-reach environments by eliminating hard-wired sensors, greatly reducing study setup time and associated costs.

- Hardened, dedicated validation console
- Asset centric data management concept
- Intuitive metro-style user onterface
- Portable validation console pre-loaded software
- Dedicated to validation tasks
- Simplified compliance and easy validation
- 21 CFR Part 11 Compliant



- Console can interface with multiple units
- Keyboard Dock lockable to Kaye's 12" Console
- Removable optical mouse function for external use
- Ethernet port




- Stand-alone operation
- Reliable data safety a smart redundancy concept
- 60 minute battery backup



Applications – Challenges – Solutions

APPLICATIONS

- Steam Sterilizer (Autoclaves)
- Dry Heat Sterilizers
- Washer Disinfectors
- Steam in Place (SIP)
- Water Cascade / Fall Sterilizers
- Incubators / Bioreactors
- Stability Chambers
- Freezers
- Freeze Dryer / Lyophilization
- Vessels



CHALLENGES

- Pharmaceutical industries are faced with increasing operational challenges
- Need for live data during study even in harsh, extreme cold, or hot temperature
- Complex and time consuming data organization
 - Cost and time of validation and re-validation
- Data Integrity – compliance with newest norms and standards
- Increased IT security and lock down of portable data
- Continually changing operation systems
 - Hardware compatibility
 - Complex software operation

MARKETS

- Pharmaceutical and Biotech Processing
- Medical Device Sterilization
- Food Processing
- Environmental Monitoring



SOLUTIONS

- Kaye ValProbe RT delivers reliable life data under harsh conditions at high or low temperatures
- Pre-loaded with Kaye software, the Kaye Validation Console is only dedicated for validation
- The system guarantees ease of use and dedicated reliable validation; allowing focus on validation tasks, not the technology
- 21 CFR part 11 compliant (data integrity)
- OS and hardware controlled and validated by Kaye
- Common software tools for Kaye hardware
- Backward compatible to existing Kaye products
- Elimination of IT control
- Intuitive metro-style touch screen interface
- Simplified validation
- Asset centric data management concept

ValProbe RT System

The ValProbe system is designed to provide easy access to process and validation study data. Loggers are programmed via the ValProbe RT base station in combination with the Kaye console.

The ValProbe RT base station communicates and collects data from 50 ValProbe RT Loggers. The system is specially designed to be extremely reliable under harsh conditions ex. 0-5 bar and -85°C to 140°C.

FEATURES

- Live data under harsh conditions via RF during validation study
- RF-range up to 150 meters
- Temperature range -85 to 400°C
- Up to 100,000 samples per sensor
- Scan rate down to 1 second
- Data transmission rate 3 seconds to 30 seconds
- ValProbe system capacity 50 loggers
- Customer interchangeable batteries
- Accuracy up to 0.1°C
- Unmatched battery life

VALPROBE RT BASE STATION

The base station serves as the interface between individual loggers and the powerful ValProbe RT system software. It is used for qualification, calibration, and verification studies. Its compact design, including a battery backup, makes it well-suited for field use or desktop applications.

The ValProbe RT Base Station is compatible with the entire product range of Kaye baths and dry wells.

Base Station Features

- Dual antenna technology/ allows installation of autoclave antenna
- Compact design for field or desktop operation
- Can operate as standalone system/internal 32 GB memory
- Power supply 100 – 240 V
- Battery backup for up to 60 minutes
- Ethernet network connection
- LED indicator confirming battery and study condition
- Logger wake-up sound indicator
- Wake-up magnet
- CE, UL certified



ValProbe RT Temperature Loggers



TEMPERATURE RANGE -85°C TO 400°C

ValProbe RT Loggers offer a remarkable temperature range from -85°C to 400°C and are proven to withstand pressures up to 5 bar, making them ideal for extreme temperature and pressure applications. They ensure accuracy with RTD technology and feature a long battery life. With programmable sample rates starting at 1 second, up to 100,000 data points per sensor can be collected. The innovative antenna design ensures reliable RF communication.

TEMPERATURE LOGGER – SINGLE, DUAL AND 5-CHANNEL BENDABLE LOGGER



Features

- Temperature range for logger sensor:
-85°C to 400°C (1 and 2-Channel);
0°C to 400°C (5-Channel)
- Single, dual and 5-channel bendable sensors
- Sensor length 12, 24, 36" (1 and 2-Channel),
24" (5-Channel)
- Sensor diameter 2.4 mm; 0.095" (1 and 2-Channel),
2 mm; 0.078" (5-Channel)

TEMPERATURE LOGGER – RIGID



Features

- Temperature range for complete logger:
-85°C to 140°C
- Single sensor only
- Sensor length 1.5, 3, 6, 9"
- Sensor diameter 3 mm; 0.118"

FLEXIBLE TEMPERATURE SENSOR LOGGER AVAILABLE AS A SINGLE, DUAL, OR 5-SENSOR LOGGER



Features

- Temperature range for complete logger:
-85°C to 140°C
- Single, dual, and 5-channel flexible
sensor available
- Sensor length 40"
- Sensor tip diameter 2.4 mm,
length 25 mm; 0.98"

FREEZE DRYER LOGGER



Features

- Temperature range for complete logger: -85°C to 140°C
- Ultra-flat surface sensor
- Surface sensor diameter 32 mm; 1.26"
- Optimized surface design also for low vacuum applications

HUMIDITY AND TEMPERATURE LOGGER



Features

- Temperature range from 0°C to 70°C
- Humidity range from 15% to 95%
- Sensor tip diameter 7.5 mm, 0.295"
- Outer filter diameter 12 mm, 0.472"
- 1 meter sensor extension cable
- Field-replaceable humidity sensor

PRESSURE AND TEMPERATURE LOGGER



Features

- Temperature range for complete logger: 0°C to 140°C
- Pressure range 0 to 5 bar, 1mbar resolution
- ¼ NPT connection fitting

CO₂ LOGGER



Features

- CO₂, RH, and temperature sensors in one measurement unit
- Enhanced electronics with extended battery life
- Data recording intervals: 10 seconds to 10 minutes
- On-site replaceable CO₂, temperature, and RH sensors
- Supported from ValProbe RT software version 1.3

ValProbe RT Specifications

KAYE VALPROBE RT GENERIC SPECIFICATIONS

Base Station Dimensions	7.6 in x 5.2 in x 2.2 in	Real-Time Clock Accuracy	< 15 sec / day
Logger Dimensions	Height: 1,9" / Diameter 1,4" 1,4 in / 3,6 in	Calibration	NVLAP/DAkkS Calibration
Logger Material	Stainless Steel 316L and Peek	Verification	Automated Verification capability
Battery	Field replaceable – 3.6V Lithium	Sensing Element	Precise Platinum RTD
Sampling Rate/Station	500 (per Channel)	Environmental Temperature	-85°C to 140°C
Data Storage	100.000 Samples retained in non-volatile memory	Environmental Pressure	0 – 5 bar absolute
		Environmental Humidity	0 – 100% condensing
		Regulatory Compliance	UL and CE

TECHNICAL SPECIFICATIONS

Sensor Type	Sensor Length / Diameter	Measurement Accuracy	Accuracy	Accuracy	Accuracy
Rigid	Single Sensor 3,6 in / 91,4 mm	1.5, 3, 6, 9" inches	0.118"; 3 mm	-85°C to 140°C	-85°C to 140°C, ±0.1°C
Bendable	Single and Dual Channel 3,6 in / 91,4 mm	12, 24, 36" inches	0.095"; 2,4 mm	-85°C to 400°C	-85°C to 140°C, ±0.1°C
	5-Channel 1,4 in / 35,7 mm	12, 24, 36" inches	0.095"; 2,4 mm	-85°C to 400°C	-85°C to 140°C, ±0.1°C
Flexible	Single and Dual Channel 1,4 in / 35,7 mm	0.095" to 36" inches	0.095"; 2,4 mm	-85°C to 400°C	-85°C to 140°C, ±0.1°C
Surface	Ultra Surface Sensor	0.095" to 36" inches	0.095"; 2,4 mm	-85°C to 400°C	-85°C to 140°C, ±0.1°C
Pressure	Single Sensor	1/4" NPT	0.095"; 2,4 mm	0.095"; 2,4 mm	120°C to 135°C, ±10mb 0°C to 140°C, ±0.1°C
Humidity	Digital Sensor	0.095" to 36" inches	0.095"; 2,4 mm	0.095"; 2,4 mm	RH: 15% to 95% RH: 25°C to 40°C ± 2.0% (15% to 95%)
CO₂	Digital Sensor	0.095" to 36" inches	0.095"; 2,4 mm	0.095"; 2,4 mm	CO ₂ : 0 to 7.5%: ±0.4% 7.5 to 9%: ±0.6% 12.5 to 20%: ±1.5%

Validation Console

A NEW FLEXIBLE APPROACH TO VALIDATION

The Kaye Validation Console is a state-of-the-art portable and rugged console, dedicated to programming, displaying, reporting, and storing Validation data. The console is pre-loaded and configured with the suite of Kaye and legacy software. It is customized to specific validations tasks. The console offers direct docking and Wi-Fi connectivity with Kaye equipment. The Kaye Validation Console brings about a new approach to tackling your software validation.

VALIDATION CONSOLE SPECIFICATIONS

Operating System / Processor / Memory

- Microsoft Windows 10 Enterprise LTSC (64 bit)
- 8th Generation Intel® Core™-i5 Processor
- 8 GB RAM

Durability IP65 Rated

- Military grade durability with improved thermal management
- Maximum protection against dust, dirt, and water ingress
- Drop-tested from 4 feet
- Temperature-tested from -20°F to 145°F (-29°C to 62°C)

Display

- 11.6-inch, FHD 1920 x 1080
- 1000 Nit outdoor-readable
- Anti-glare, anti-smudge, polarizer
- Glove-capable touchscreen

System Storage

- 256GB M.2 Solid State Drive (SSD)

Integrated Communications

- Intel® Wireless-AC 9560
- 802.11ac with Bluetooth 5.0

I/O Ports

- Docking Connector
- 1 - USB 3.1 Type-A with power delivery
- 1 - USB 3.0 Type-C port with DisplayPort Alt Mode / PowerShare
- 1 - Combo mic/headphone jack
- 256GB M.2 Solid State Drive (SSD)

Embedded I/O

- On-board camera capability of taking pictures with console
- 5 MP RGB + IR FHD webcam with privacy shutter / 8 MP rear camera with flash and dual microphone

Dimensions / Weight⁽¹⁾

- 7.99 in x 12.29 in x .96 in (203 mm x 312 mm x 24,4 mm)
- 2.93 lbs (1.33 kg)⁽¹⁾

Battery

- Battery life up to 6 hours⁽²⁾

Backwards Compatibility

- Can run with Kaye Validator and Kaye ValProbe software

1. Weight represents approximate system weight measured with a 34Whr battery. Actual system weight may vary depending on component and manufacturing variability.

2. Battery life varies by configuration, applications in use, utilized features, and operating conditions. Maximum battery capacity decreases with time and use.

Two ways to connect the Validation Console to ValProbe RT

1. DOCKING MODE (STAND-ALONE)

The console sits in the keyboard docking and can connect directly to the ValProbe RT Base Station. The console battery charges while docked.



2. NETWORK MODE

The Validation Console can connect to a local network by using ethernet or Wi-Fi connection. One validation console can handle multiple Kaye validation systems simultaneously.



The Kaye Validation Console can establish wireless connections* by utilizing any kind of available Wi-Fi infrastructure.

This feature simplifies your daily routine work. You can access live data wirelessly on the console screen. You can start or stop studies and read live data from a Kaye ValProbe RT system in a cleanroom without entering the room.






* This feature is not available in some countries. Please contact your local Kaye support for details.

ValProbe RT Software


ASSET CENTRIC DATA MANAGEMENT

The Kaye ValProbe RT includes an intuitive Asset Centric Data Management concept which allows you to store and access your data faster and more efficiently. Each individual process that you validate, whether an autoclave or freezer etc., can be setup and defined as an asset. All files and data related to an asset, such as setups, verifications, or study files, are organized and accessed in one single screen around the basic asset data. It is also possible to upload additional documents such as standard operation procedures or certificates and associate them with the asset. Assets can be sorted and searched by type, location, manufacturer etc. for easy access.



EQUIPMENT ASSETS


With the Kaye ValProbe RT you can define assets for each piece of Kaye Validation equipment. Data such as serial numbers and calibration due dates can be defined. The software automatically notifies the user when calibrations are due. The equipment search function uses the Kaye serial number, that is automatically retrieved as part of the study file, to find related files. Using just one fingertip you can have a list of qualification studies where the equipment asset was used.



QUALIFICATION / STUDY

The Kaye Validation Console can connect to a ValProbe RT system directly through the docking station of the console or via WiFi to the network connected base station. It enables the user to transfer setups, start studies, and monitor live data or read finished studies. After starting a study, the ValProbe RT base station runs the tasks independently.

One Kaye Validation Console can control several validation systems in parallel and one validation system can handle several consoles. While connected to ValProbe RT the user can see the live data in list or graphical view, group based calculation, and event messages. Any connected hardware is displayed with a serial number.



SENSOR VERIFICATION


Kaye, the original creator of the Automatic Logger Verification feature has included enhancements eliminating manual methods of logger verification resulting in better accuracy.

Kaye ValProbe RT is backward compatible with existing Kaye IRTD and calibration baths. The automatic verification feature minimizes training and ensures accurate and repeatable verifications, all while being well documented.


Select only loggers you want to verify. Defining a verification setup lets you verify a large number of loggers among all those displayed in equipment assets.



Set the criteria for a logger verification – the ValProbe RT system allows you up to six independent temperature verification points.



The console displays the entire verification process on one screen. Data fields change color to show the progress of stability and deviation for each logger. A status window lists each step and indicates where the system is in the process.



Kaye Common Reporting Tool

The Kaye Validation Console includes an extensive and flexible Common Reporting Tool used to analyze and document your critical Validation studies directly. The Reporting Tool is seamlessly integrated into the ValProbe RT software. It can be used to analyze and document ValProbe RT studies directly with the Kaye console. Additionally, it is available for installation on any Windows based computer to enable reporting in the convenience of your office setup. The Kaye Reporting Tool is designed to ensure that the proven and accepted formats of the ValProbe summary, detailed, and calibration reports are maintained. Enhancements to graphing reports, setup reports, as well as new reports such as ValProbe RT wiring layout, Pass & Fail reports and the AFNOR FD X15-140 / IEC 60068 conform report for climatic chambers provide fast and detailed ways of analyzing your data. The Kaye Common Reporting Tool can merge up to three study files into one single report. Reports can be previewed, printed, saved as a PDF or Excel file.

CONFIGURATION CHOICES

Prior to generating reports the Reporting Tool provides a host of configuration choices:

- Sensors included in report
- Sensors separated by groups
- Sensor placement and description
- Define cycles (qualification, exposure, etc.)
- Calculations (statistical, lethality, saturation, MKT etc.)
- Header / footers
- Graphing
- Templates
- Pass / fail criteria

These features provide you with maximum flexibility to get the data and calculations you require in the correct formats to meet your Validation reporting needs.

REPORTING

- ValProbe RT Wiring Layout
- Setup Report
- Verification Report
- Graph Report
- Detailed Report:
 - Statistical
 - Lethality
 - Saturation
 - MKT
 - Summary Report
 - Audit Trail Report
 - Pass / Fail Report
 - AFNOR FD X15-140 / IEC 60068 Climatic Chamber Report

KAYE

ValProbe RT Temperature Verification Report

Printed on 10-Jun-2024 at 15:03:53 by User1

Temperature Logger TW58-T

Verification 10-Jun-2024 at 14:47:07 by User1

Company: KAYE

Logger Firmware Version: 2.3.5

Software Version: 1.3.0.34

SOP / Protocol #:

Battery life: 18 %

Automatic Verification

Temperature Std: Kaye IRTD

Serial No: AA250

Cal Date: 13-Nov-2023

Bath: LTR-90

Summary Verification Results: Passed

SP1: Passed

SP2: N/A

SP3: N/A

SP4: N/A

SP5: N/A

SP6: N/A

Start Time: 14:47:07

Time Zone: UTC-06:00

Setpoint 1:

40.00 °C

Passed

Stability Criteria:

Sensor Stability: 0.50 DC for 3 minutes

IRTD Stability: 0.012 DC for 3 minutes

Additional time of Stability: 6 minutes

Deviation Criteria:

0.50 DC for 3 minutes

Stability Evaluation:

Time of Stability: 14:54:40

Sensor Temperature: 40.11 DC

IRTD Temperature: 40.038 DC

Sensor Deviation From IRTD: 0.07 DC

Sensor Stability: 0.04 DC

IRTD Stability: 0.002 DC

Deviation Evaluation:

Criteria: 0.50 °C for 3 minutes

Maximum Deviation: 0.11


Time	IRTD (°C)	Sensor (°C)	Dev (°C)	Time	IRTD (°C)	Sensor (°C)	Dev (°C)	Time	IRTD (°C)	Sensor (°C)	Dev (°C)
14:54:50	40.037	40.11	0.07	14:55:00	40.038	40.12	0.08	14:55:10	40.038	40.11	0.07
14:55:20	40.037	40.11	0.07	14:55:30	40.037	40.12	0.08	14:55:40	40.038	40.11	0.07
14:55:50	40.038	40.13	0.09	14:56:00	40.038	40.15	0.11	14:56:10	40.038	40.13	0.09
14:56:20	40.038	40.12	0.08	14:56:30	40.039	40.11	0.07	14:56:40	40.038	40.12	0.08
14:56:50	40.038	40.13	0.09	14:57:00	40.038	40.13	0.09	14:57:10	40.038	40.12	0.08
14:57:20	40.039	40.13	0.09	14:57:30	40.038	40.12	0.08	14:57:40	40.038	40.13	0.09

Verification Report

ValProbe RT Wiring Layout

Asset Name: Fedegari Test1

KAYE



Sensor Mapping Table


Number	Sensor Name	Description
1	Type T1	Type T
2	Type T2	Type T
3	Type T3	Type T
4	Type T4	Type T
5	Type T5	Type T
6	Type T6	Type T
7	Type T7	Type T
8	Type T8	Type T
9	Type T9	Type T
10	Type T10	Type T
11	Type T11	Type T
12	Type T12	Type T

ValProbe RT Wiring Layout

KAYE ValProbe RT Graph Report

Printed on 14-Dec-2018 at 14:21:51 by Tester

Study Name: SchanneSetup Company: KAYE ValProbe RT Version: 1.0.0.18
 Asset ID: 123 SOP/Protocol #: 456 ValProbe RT Report Version: 1.0.0.5
 Programmed by: a Date: 19-Nov-2018 Comments:



Sensor Type	Sensor Label	Sensor SN	Sensor Description
Temperature	tx-1	SN00013-A	
Temperature	tx-2	SN00013-B	
Temperature	tx-3	SN00013-C	
Temperature	tx-4	SN00013-D	

Graph Report

KAYE ValProbe RT Qualification Summary Report

Amphenol

Printed on 20-Jun-2018 at 11:12:51 by a

Study Name: 1TempQual Company: KAYE ValProbe RT Version:
 Asset ID: 1234 SOP/Protocol #: 456 ValProbe RT Report Version:
 Programmed by: a Date: 20-Jun-2018 11:12:51 Asset: 1

Comments

Lethality has been selected with the following criteria:

Base Temperature: 125.1 D Value: 1.00 Z Value: 10.0
 Lethality Calculated: During Entire Cycle
 Lethality calculations are performed in minutes

Calculations in Summary report is based on 5 Seconds sampling rate:

Base Station Details

Name: 1a102 Location: 1a1 Location: 1a1
 Serial No: Model No: Site No:
 IP Address: 127.0.0.1 MAC Address:

Loggers Included in Study

Serial No	MAC Address	Logger Type	MFG Cal Date	Firmware	RT Strength	Battery Life
SH00003	00-4B-D4-VU-0A-00-7B-1B	2 Ch Temp Pressure	01-01-2001	2.10	0	30
SH00003	00-4B-D4-VU-0A-00-7B-1B	2 Ch Temp Pressure	01-01-2001	2.10	0	30

Performed By: _____ Date: _____
 Reviewed By: _____ Date: _____ Page 1 of 10

Qualification Report

FD X15-140 Report

Printed on 21-Feb-2018 at 11:33:30 by a

Graph FD X15-140




AFNOR FD X15-140 Compliant Graph

KAYE ValProbe RT Graph Report

Printed on 14-Dec-2018 at 14:25:51 by Tester

Study Name: SchanneSetup Company: KAYE ValProbe RT Version: 1.0.0.1
 Asset ID: 123 SOP/Protocol #: 456 ValProbe RT Report Version: 1.0.0.1
 Programmed by: a Date: 19-Nov-2018 Comments:



Sensor Type	Sensor Label	Sensor SN	Sensor Description
Temperature	tx-1	SN00013-A	
Temperature	tx-2	SN00013-B	
Temperature	tx-3	SN00013-C	
Temperature	tx-4	SN00013-D	
Temperature	tx-5	SN00013-E	


Graph Lethality Report

Flexible and Compliant


ELECTRONIC SIGNATURE

Kaye ValProbe RT is a state-of-the-art validation system designed to meet worldwide regulations and guidelines on Thermal Validation and Data Integrity. All recorded data, including calibration offsets, set-up parameters, and administrative tasks are saved in secure, encrypted, tamper-proof electronic records in a format accessible only through the system software. In addition to pre-configured privilege levels, it is possible to explicitly set permissions for each user.

With data synchronization to a shared folder it is possible to exchange configuration and data files like your assets, setups, and study files with other Kaye validation consoles. The Kaye ValProbe RT can synchronize a user database and also merge audit trails of several consoles enabling sorting, searching, and printing of department-wide audit trails, for example, a list of all failed login attempts within a specified time period across all synchronized Kaye validation consoles. Every console has a unique but customizable machine ID for identification.



User Management



Policies

KAYE Audit Trail Report
Machine ID: 88P20-035-09038844200 Duration: 14-Dec-2018 to 14-Dec-2018 Printed on 14-Dec-2018 at 17:05:08 by Tester

Audit Trail						
Logged In User ID	User Name	Date / Time	Actions	User Comment - Audit Trail	Device Details	MM ID
1	Tester	14-Dec-2018 at 09:24:14	User ID: 10 - User Name: "Tester" logged in to the "UserManagement" operation in "UserManagement" console		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:25:31	User ID: 10 - User Name: "Tester" logged in to the "UserManagement" operation in "UserManagement" console		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:25:18	User ID: 10 - User Name: "Tester" logged in to the "UserManagement" operation in "UserManagement" console		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:25:08	User ID: 10 - User Name: "Tester" logged in to the "UserManagement" operation in "UserManagement" console		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:25:03	User ID: 10 - User Name: "Tester" logged in to the "UserManagement" operation in "UserManagement" console		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:24:45	Application Logout		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:24:01	Logout attempt failed for User ID: 10, User Name: "Tester"		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:23:13	User ID: 10 - User Name: "Tester" logged in to the "QualificationStart" operation in "Qualification" console		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:23:02	User ID: 10 - User Name: "Tester" logged in to the "QualificationStart" operation in "Qualification" console		88P20-035-09038844200	
1	Tester	14-Dec-2018 at 09:23:08	Qualification Started for User ID: 10, User Name: "Tester"		88P20-035-09038844200	

Page 1 of 10

Audit Trail Report

System Documentation

QUALITY CONTROL DOCUMENTS

Kaye's quality policy, the ISO 9001 implementation and certificate, and document control standard operating procedures (SOPs)

DEVELOPMENT PROCEDURES

Design control and project management SOPs, and functional specifications

QUALITY ASSURANCE PROCEDURES

Test plan and test case procedures

RELEASE DOCUMENTS

Quality assurance certification and product release notices

QUALITY ASSURANCE TEST DOCUMENTATION

Quality assurance test plan and test cases

IQ/OQ PROTOCOL

The Installation Qualification/Operational Qualification Protocol defines a set of procedures to ensure that the Kaye ValProbe RT system is properly installed and operated according to Kaye's recommendations, and is adequately documented and controlled according to cGMP requirements. The documents are provided in hard copy and on CD, allowing users to modify the documentation to suit specific organizational requirements.

The IQ/OQ Protocol includes the following:

- Installation Qualification document
- Operational Qualification document
- Operational Qualification document – Report
- Standard Operating Procedures document

If you prefer to have IQ/OQ executed by qualified Kaye technicians we also provide Validation IQ/OQ on-site execution.

VALIDATION REFERENCE

The Kaye ValProbe RT system is supported with documentation that verifies a fully validated system, including software, hardware, and firmware.

The Validation Reference Binder provides a comprehensive overview of the Amphenol Quality Policy, description of ISO 9001 implementation, and support procedures, and standards for the development, testing, and maintenance of hardware and software. quality control documents, development procedures, quality assurance procedures, release documents, and quality assurance test documentation are all included.

The Validation Reference is a serialized document, ensuring that registered users automatically receive notification and updates to keep documentation current. The result is a summary of information you would obtain by conducting an audit at Amphenol's facility – complete, well organized, neatly packaged, and immediately accessible.

ValProbe RT Onsite Verification

HIGH ACCURACY REFERENCING

Kaye's temperature calibration equipment is designed specifically to maximize overall system accuracy. Calibration equipment includes temperature references with superior uniformity, traceable intelligent RTD standards, and validation software to communicate with the hardware.

FAST / ACCURATE REFERENCING

System performance data is only as good as the accuracy of the baseline measurement and inaccurate measurements have no place in pharmaceutical and biotech processing.

Kaye baths, dry wells, and IRTD temp standards offer unparalleled accuracy over a wide temperature range and reliability to meet your validation and verification needs.

INTELLIGENT RTD STANDARD

The IRTD Temperature Standard (IRTD-400) is a NIST/DAkkS-traceable instrument that is calibrated over the range of - 196°C to 420°C. It is accurate to $\pm 0.025^\circ\text{C}$ over the entire operating range. Communicating directly with the console software, the IRTD-400 eliminates the potential for human error, assuring accurate and traceable measurements.



KAYE CTR-25

- Temp Range: -25°C to 140°C (closed cover)
- Verification of up to 10 rigid ValProbe RT loggers



KAYE LTR-150


- Temp Range: -30°C to 150°C
- Liquid micro bath tub with sensor cage and magnetic stirrer can hold ValProbe RT rigid loggers



Accessories

KAYE VALPROBE RT TRANSPORT / STORAGE TRAY

The ValProbe RT transport/storage tray is an accessory designed to simplify the carrying, storage, and management of Kaye ValProbe RT loggers during use. The ValProbe RT transport/storage tray can accommodate up to 20 Kaye ValProbe RT loggers of any type.



KAYE INSULATING CANISTER

Use the Insulating Canister in combination with minimum the 12" bendable temperature loggers for a perfect solution for dry heat applications.

Performance (max. exposure time)

Temperature	1 and 2-channel logger	5-channel logger
360°C	40 min	35 min
300°C	60 min	55 min
250°C	90 min	80 min
200°C	120 min	120 min
170°C	180 min	180 min



KAYE SHIPPING CASE

Protect your validation equipment and store it safely when not being used.



KAYE AUTOCLAVE ANTENNA

The Kaye Autoclave Antenna provides improved signal strength for challenging applications like large autoclaves or vessel in vessel setups. It is steam proven and can be installed via the standard Kaye Feedthru.



Kaye representative contact:

Request a demo:

AUTHORIZED SALES AND SERVICE (MALAYSIA)

ENVIROTERM SDN. BHD.

HEAD OFFICE & TRAINING CENTER

Lot 5028, Jalan 18/62, Taman Sri Serdang,
43300 Seri Kembangan, Selangor D.E.

T: +603 8210 8338

E: sales@envirotterm.com

W: www.envirotterm.com

MAIN SERVICE CENTER

Lot 5035, Jalan 18/62, Taman Sri Serdang,
43300 Seri Kembangan, Selangor D.E.

T: +603 8210 8338

NORTHERN OFFICE & SERVICE CENTER

5112, Jalan Capri, Taman Capri,
12100 Butterworth, Pulau Pinang.

T: +604 331 1371

SOUTHERN OFFICE

20-09, Austine 18, Jalan Perdana 3,
Taman Austine Perdana,
81100 Johor Bahru, Johor D.T.

T: +607 364 8080

